

1	2	3	4	5	6	7	8
上海冠显光电科技有限公司 Top Display Optoelectronics Co., Ltd		DESIGN: (设计) Huang	CHECKED: (检查)	APPROVED: (批准)	SPECIFICATION		
Date: (日期) 2017.12.18		Page: (页数) 1/1	图纸视角:	CUSTOMER'S CODE: (客户型号) TL01000V01-H1136A	EDITION: (版本号)		01
				TDO'S CODE: (冠显料号)	EDITION: (版本号)		
Pin Assignment							
A	B	C	D	A	B	C	D
NO.	SYMBOL						
1	TPO						
2	TP1						
3	SDA						
4	SCL						
5	RS						
6	RES						
7	CS						
8	GND						
9	NC						
10	VCC						
11	LEDK						
12	LEDA						
13	GND						
Notes: 1. Unit: mm. 2. Modification rev.number. 3. All radii without dimension R0.3mm. 4. All draft angles to be 1.5° 5. Unspecified Tolerances is : ±0.30mm. 6. Driver IC: LCD(ST7735S) 7. LCD Driver Voltage : 2.8±0.3V 8. BACK LIGHT: LED (WHITE). 9. Operating Temperature : -20°-- +70°C 10. Storage Temperature : -30°-- +80°C 11. Requirements on Environmental Protection: ROHS							
1	2	3	4	5	6	7	8